EV9625-01

CV Filter Cartridge

Problem solving and special application cartridge

CV Replacement Cartridge: EV9625-01

BENEFITS

Special application cartridge is ideal for extra dirty water conditions

Five micron filter features precoat technology

Captures larger dirt particles

Reduces chlorine taste and odor and other offensive contaminants

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

INSTALLATION TIPS

Install vertically with cartridge hanging down

Allow 2-1/2" clearance below the cartridge for easy cartridge replacement

Flush cartridge by running water through filter for three minutes at full flow

OPERATION TIPS

Change cartridges on a regular 6 month preventative maintenance program

Change cartridges when capacity is reached or when pressure falls below 10 psi

Always flush the filter cartridge at time of installation and cartridge change

APPLICATION/SIZING

Problem solving and special application cartridge

For extraordinary water conditions

Rated Capacity: 7,500 gallons (28,400L)

CV Filter Cartridge

SPECIFICATIONS

Overall Dimensions:
20.75"H x 3.25"Diameter

Service Flow Rate:
Maximum 1.67 gpm (6.3 Lpm)

Rated Capacity: 7,500 gallons

Pressure Requirements:
10 - 125 psi (0.7 – 8.6 bar), non-shock

Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required



The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.

INDEPENDENTLY NSF CERTIFIED

System Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of:

Standard No. 42: Aesthetic Effects
Chemical Unit
Taste and Odor Reduction
Chlorine Reduction
Mechanical Filtration Unit
Particulate Reduction, Class II

EVERPURE®

EVERPURE, LLC
1040 Muirfield Drive
Hanover Park, Illinois 60133
Toll Free (800) 323-7873
Tel (630) 307-3000
Fax (630) 307-3030
http://www.everpure.com

In Europe:
N.V. EVERPURE (EUROPE) S.A.
Industriepark Wolfstee
Toekomstlaan 30
B-2200 Herentals
Belgium
Tel 32 -14-283500
Fax 32-14-283505

In Japan:
EVERPURE JAPAN LLC
Hashimoto MN Bldg. 7F
3-25-1 Hashimoto Sagamihara-Shi
Kanagawa 229-1103
Japan
Tel 81-(0)42-775-3011
Fax 81-(0)42-775-3015

Everpure, LLC
1040 Muirfield Drive
Hanover Park, IL 60133
Ph: 630-307-3000 Fax: 630-307-3030